

## SG-2G-WH

### smartengine Universal Gateway Wiring Harness, Generation 2



## GENERAL SPECIFICATIONS

<b>Brand</b>	wtec
<b>Product Type</b>	Wiring harness
<b>Application</b>	Connects smartgateways to rib relays
<b>Package Quantity</b>	1
<b>Color</b>	White

## SG-2G-WH

### smartengine Universal Gateway Wiring Harness, Generation 2

#### DIMENSIONS

Length	2 m   7 ft
Weight	0.73 kg   1.60 lb

#### MECHANICAL SPECIFICATIONS

Conductor Gauge, stranded	18 AWG
Conductors, qty	8
Contact Connector Interface	Stripped pigtail
Gateway Connector Interface	10-pin connector
Material Type	Copper

#### ENVIRONMENTAL SPECIFICATIONS

Environmental Space	Indoor   Plenum
Flammability Rating	CMP   NFPA 262   UL 910
Operating Temperature	0°C to +50°C (+32°F to +122°F)
Relative Humidity	10%-80%, non-condensing
Safety Standard	AS/NZS CISPR 22   c-UL-us   CE   CEC Title 24-2008   IEC 60950   IEC 61000-4.5, Class 3   UL 60950   UL 924   UL-us   US FCC Part 15, Class A

#### REGULATORY COMPLIANCE/CERTIFICATIONS

Agency	Classification
RoHS 2011/65/EU	Compliant

