

Issue 20190322 – March 2019

SG-2G-WH



smartengine Universal Gateway Wiring Harness,
Generation 2

GENERAL SPECIFICATIONS

Brand..... smartengine
Generation..... 2
Product Type Wiring harness
Application Connects smartengine universal gateway to dry contact
Package Quantity..... 1
Ordering Note Requires universal gateway
Colour White

DIMENSIONS

Length..... 2 m | 7 ft
Weight..... 0.73 kg | 1.60 lb

MECHANICAL SPECIFICATIONS

Conductor Gauge, stranded..... 18 AWG
Conductors, qty 8
Contact Connector Interface Stripped pigtail
Gateway Connector Interface... 10-pin connector
Material Type..... Copper

Issue 20190322 – March 2019

SG-2G-WH

ENVIRONMENTAL SPECIFICATIONS

Environmental Space..... Indoor | Plenum
Flammability Rating CMP | NFPA 262 | UL 910
Operating Temperature 0°C to +50°C (+32°F to +122°F)
Relative Humidity 10%-80%, non-condensing
Safety Standard..... AS/NZS CISPR 22 | c-UL-us | CE | CEC Title 24-2008 | IEC 60950 | IEC 61000-4.5, Class 3 | UL 60950 | UL 924 | UL-us | US FCC Part 15, Class A

SG-2G-WH

REGULATORY COMPLIANCE/CERTIFICATIONS

Agency	Classification
RoHS 2011/65/EU	Compliant

